

▶ **FDE / FDEP Price Computing Scale**



⊙ **Features**

- Digital calibration
- Vendor and customer sides LCD or LED displays (LCD display with LED backlight)
- Low power and charging status indication
- Water channel designed underneath the platter to give a better protection against water running into the scale
- Unique sealing rings designed to prevent dust, dirt, cockroaches and water from entering the scale, thereby improving reliability and hygiene
- Special design for power switch prevents moisture getting inside the scale for better performance stability and reliability
- Special sunken power coil outlet design to prevent water running into the socket to improve safety and reliability
- Easily adjusted leveling feet for stability of the scale
- Money change
- Kilogram (kg) weighing mode
- Up to 99 data accumulation and 10 data recall

⊙ **Specifications**

1/3 000 display resolution (Dual range model and 1/6 000 display resolution available)

Model	Capacity	Division
FDE / FDEP-110 -3	3kg	1g
FDE / FDEP-110 -6	6kg	2g
FDE / FDEP-110 -15	15kg	5g
FDE / FDEP-110 -30	30kg	10g
Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F)		
Power Source: AC 110V/230V (±10%) + DC 6V/4 Ah rechargeable battery		
Dimensions: FDE: 300 × 110 × 330mm (W × H × D) FDEP: 300 × 530 × 330mm (W × H × D)		
Platter Size: 300 × 225mm		
Display: LCD, 5, 5, 6 Digits. Main display: 18mm (Height). Pole display: 14mm. LED backlight (Vendor side for standard)		