

LP7516

Plastic Housing Weighing Indicator



※ Technical Parameters

- ◆ Display: 6-digit 20mm LED or 25mm LCD with backlight
- ◆ Accuracy class: OIML II
- ◆ AD convert: Σ , Δ , 24 bit
- ◆ Input voltage: -7mV-12.8mV
- ◆ Resolving: display 15,000, internal code 1,000,000
- ◆ Minimum resolution: 1 μ V/e
- ◆ Excitation voltage: DC3.3V
- ◆ Load cell interface: 4-wire, 1-4 350 Ω analog load cell(s)
- ◆ Power supply: AC110/220V 50/60Hz or built-in 4V/4Ah lead acid battery
- ◆ Work environment: -10°C ~+40°C, $\leq$ 85%RH
- ◆ Battery enduring life: 50 hours for continuously use (with 4 350 Ω analog load cells)

※ Options

- ◆ Second display interface: serial RS232
- ◆ Communication interface: RS232, baud rate 600-9,600 (optional)
- ◆ Printing interface: shared with serial interface, can be connected to serial printer (optional: desktop printer)
- ◆ Bluetooth

※ Application for

- ◆ Electronic floor scale, bench scale, logistics scale, pet scale, load cells, etc.

※ Product Functions:



※ Dimensions:

- ◆ Unit (mm)

